2022

RENEGADE X

High-performance and high-tech features for the most demanding rider.





RENEGADE® X® 900 ACE® TURBO R SHOWN

// WHAT'S NEW

- Rotax $^{\circ}$ 900 ACE[™] Turbo R with cable throttle housing and electro-mechanical reverse
- Standard with two sets of LinQ attachment points

// PACKAGE HIGHLIGHTS

- Rotax® 850 E-TEC® and 600R E-TEC® engines
- High-performance shock package
- 7.8 in. wide LCD display with BRP Connect available [850 E-TEC and 900 ACE Turbo R only]
- RAS™ X front suspension
- rMotion™ X rear suspension

- Electric starter
- pDrive™ clutch
- Forward adjustable riser
- Transparent handguards
- Open toe-hold

- Ski choices: Pilot™ X or Pilot™ TX (available with QAS on 850 E-TEC and 900 ACE Turbo R)
- Backlit multifunction handlebar controls
- Optional adjustment package: rMotion™ X Quick Adjust™ system and Pilot™ TX skis (850 E-TEC and 900 ACE Turbo R)

ROTAX® Engine	850 E-TEC®	600R E-TEC®	900 ACE™ Turbo r
Engine details	Liquid-cooled, two-stroke, eRAVE™	Liquid-cooled, two-stroke, eRAVE™	Liquid-cooled, four-stroke D.O.H.C., dry sump, turbocharged
Horsepower	165	125	180
Cylinders - Displacement	2 - 849 cc	2 - 599.4 cc	3 - 899 cc
Bore - Stroke	82 mm - 80.4 mm	72.3 mm - 73 mm	73 mm - 69.7 mm
Carburation	E-TEC® direct injection with additional booster injectors	E-TEC® direct injection	EFI
Fuel type – Octane	Premium unleaded - 91	Premium unleaded - 91	Premium unleaded - 91
Fuel tank	36 L/9.5 US gal	36 L/9.5 US gal	36 L/9.5 US gal
Oil tank capacity	3.4 L/3.6 qt	3.4 L/3.6 qt	3.3 L/35 qt
POWERTRAIN			
Drive clutch Driven clutch	pDrive™ with clickers QRS Vent	pDrive™ with clickers QRS	pDrive™ QRS Vent
Drive sprocket pitch	73 mm/2.86 in.	73 mm/2.86 in.	73 mm/2.86 in.
DRY WEIGHT			
Dry weight	221 kg/486 lb	214 kg/470 lb	238 kg/524 lb

ENGINE	850 E-1EC	BUUK E-TEC	TURBO R	
Engine details	Liquid-cooled, two-stroke, eRAVE™	Liquid-cooled, two-stroke, eRAVE™	Liquid-cooled, four-stroke D.O.H.C., dry sump, turbocharged	
Horsepower	165	125	180	
Cylinders - Displacement	2 - 849 cc	2 - 599.4 cc	3 - 899 cc	
Bore – Stroke	82 mm - 80.4 mm	72.3 mm - 73 mm	73 mm - 69.7 mm	
Carburation	E-TEC® direct injection with additional booster injectors	E-TEC® direct injection	EFI	
Fuel type – Octane	Premium unleaded - 91	Premium unleaded - 91	Premium unleaded - 91	
Fuel tank	36 L/9.5 US gal	36 L/9.5 US gal	36 L/9.5 US gal	
Oil tank capacity	3.4 L/3.6 qt	3.4 L/3.6 qt	3.3 L/35 qt	
POWERTRAIN				
Drive clutch	pDrive™ with clickers	pDrive™ with clickers	pDrive™	
Driven clutch	QRS Vent	QRS	QRS Vent	
Drive sprocket pitch	73 mm/2.86 in.	73 mm/2.86 in.	73 mm/2.86 in.	
DRY WEIGHT				
Dry weight	221 kg/486 lb	214 kg/470 lb	238 kg/524 lb	
DIMENSIONS				
Overall vehicle length	3,038 mm/119.6 in.			
Overall vehicle width	1,209 - 1,232 - 1,255 mm/47.6 - 48.5 - 49.4 in.			
Overall vehicle height	1,267 mm/49.9 in.			
Ski stance	1,069 - 1,092 - 1,115 mm/42.1 - 43 - 43.9 in.			
Track	RipSaw†:			
(Length x Width x Profile)	137 x 15 x 1.25 in.			
	Ice Ripper XT:			
		137 x 15 x 1.25 in. opt.		
		137 x 15 x 1.5 in. opt.		

COLOR

Sunburst Yellow / Black	
Black	
SUSPENSION	
Front suspension	RAS™ X
Front shock	HPG™ Plus
Front suspension travel	243 mm/9.6 in.
Rear suspension	rMotion™ X with QAS (optional)
Center shock	HPG™ Plus
Rear shock	KYB† PRO 36 Easy-Adjust
Rear suspension travel	292 mm/11.5 in.
FEATURES	
Frame	REV® Gen4

FEATURES	
Frame	REV® Gen4
Bodywork	Narrow design (2-stroke engines) Wide design (4-stroke engines)
Skis	Pilot™ X Pilot™ TX (optional)
Seating	Trail performance (2-stroke engines) Trail with storage (4-stroke engines)
Handlebar	U-shaped aluminum with J-hooks/ Transparent handguards
Riser block height	Adjustable-120 mm/4.7 in.
Starter	Electric
Reverse	RER™ (2-stroke engines) Electro-mechanic (4-stroke engines)
Brake system	Brembo racing brake with stainless- steel braided brake line
Heated throttle lever/grips	Standard
Gauge type	7.2 in. wide digital display 7.8 in. wide LCD color display (opt.)
Windshield	360 mm/14 in.
Runner – Carbide	Round 7/16 – 4 in.
Bumpers (front/rear)	Std/Std

2022 RENEGADE® X®

// FEATURE HIGHLIGHTS



1 Rotax® 850 E-TEC® and 900 ACE™ Turbo R engines

The most powerful 2-stroke and 4-stroke options in the lineup, offering top performance for the most demanding riders.



2 Premium shock package

HPG Plus front and center shocks. KYB PRO 36 EA rear shock featuring compression adjustment with easy-adjust knob. All four shocks are aluminum and rebuildable/revalvable.





3 Adjustment package

Totally transforms the handling characteristics of the sled according to riding style or conditions with unmatched ease. Includes rMotion X Quick Adjust System and Pilot TX skis.



RENEGADE® X-RS® 850 E-TEC® SHOWN



4 rMotion™ X rear suspension

Built upon the same principles rMotion suspensions are renowned for, and then some. Completely redesigned for unmatched big-bump absorption and incredible comfort. Longer front arm with exclusive adjustable-angle design fits ideally with RAS X front suspension, creating superior cornering on trail.



5 Large panoramic 7.8 in. wide LCD color display available

Wide-screen full-color display lets riders truly customize their ride from behind the bars. Choose your preferred sled info, and see app integrated-information in a split-screen format with GPS, Bluetooth music, helmet-to-helmet communication and more.

(See website for image)

6 Three track choices

Superior performance assured with your choice of factory-installed Ripsaw or studded Ice Ripper tracks



