## 2022

## **EXPEDITION° SPORT**

Ultra-responsive chassis for on- or off-trail rides and extensive array of sport-utility and 2-up features.



## // PACKAGE HIGHLIGHTS

- Rotax® 900 ACE™ engine with 420W magneto
- pDrive™ clutch
- 4.5-in. digital display
- RAS  $^{\text{\tiny TM}}$  3 front suspension
- SC<sup>™</sup>-5U articulating rear suspension with locking mechanism (no tool required)
- Brembo brake with braided stainless-steel brake line
- Heavy duty rear bumper with hitch
- Air radiator with fan and engine oil cooler
- 2-up seat with removable LinQ passenger backrest and handholds

COLOR

- Deep-snow running boards with large openings
- NEW standard with 2 sets of LinQ attachment points
- Adjustable ski stance
- Pilot™ DS 2 skis

ROTAX® ENGINE	900 ACE™	
Engine details	Liquid-cooled,	
	four-stroke D.O.H.C.,	
	dry sump	
Horsepower	95	
Cylinders – Displacement	3 - 899 cc	
Bore - Stroke	73 mm - 69.7 mm	
Carburation	EFI	
Fuel type – Octane	Unleaded – 95	
Fuel tank	36 L	
Oil tank capacity	3.3 L	
POWERTRAIN Drive clutch	pDrive™ with slider shoes	
Driven clutch	QRS	
Drive sprocket pitch	73 mm	
DIMENSIONS		
Overall vehicle length	3,309 mm	
Overall vehicle width	1,180 to 1,220 mm	
Overall vehicle height	1,515 mm	
Ski stance	975 or 1,020 mm	
Track	Charger:	
(Length x Width x Profile)	154 x 16 x 1.5 in.	

SUSPENSION		
Front suspension	RAS™ 3	
Front shock	HPG™	
Front suspension travel	210 mm	
Rear suspension	SC™-5U	
Center shock	HPG	
Rear shock	HPG	
Rear suspension travel	239 mm	

Frame	REV® Gen4
Bodywork	Wide design
Skis	Pilot™ DS 2
Seating	2-up
Handlebar	U-shaped aluminum with J-hooks
Riser block height	145 mm
Starter	Electric
Reverse	Mechanical
Air radiator	Fan
Brake system	Brembo brake with stainless-steel braided brake line
Heated throttle lever/grips	Standard (driver only)
Gauge type	4.5 in. digital display
Windshield	585 mm
Runner – Carbide	Square 3/8 - 102 mm
Bumpers (front/rear)	Std/Heavy Duty with J-hook type hitch



