

2022 RENEGADE® SPORT

Value-oriented with exceptional handling, bump capability and light off-trail riding.



RENEGADE® SPORT
600 ACE™ SHOWN

// PACKAGE HIGHLIGHTS

- Rotax® 600 ACE™ with 420W magneto
- HPG™ rear shock
- 4.5 in. digital display
- RAS™ 3 front suspension
- SC™-5M rear suspension
- Standard electric start
- Glove box with 4 L of storage
- Low windshield (360 mm)
- D.E.S.S.™ key
- Brembo brake with braided stainless-steel brake line
- Ergo-step side panels
- U-shaped aluminum handlebar with integrated J-hooks
- Pilot DS 2 skis
- NEW standard with two sets of LinQ attachment points

ROTAX® ENGINE

600 ACE™

Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Horsepower	62
Cylinders - Displacement	2 - 600 cc
Bore - Stroke	74 mm - 69.7 mm
Carburation	EFI
Fuel type - Octane	Unleaded - 95
Fuel tank	36 L
Oil tank capacity	2.1 L

POWERTRAIN

Drive clutch	eDrive™ II
Driven clutch	QRS
Drive sprocket pitch	73 mm

DIMENSIONS

Overall vehicle length	3,038 mm
Overall vehicle width	1,217 mm
Overall vehicle height	1,267 mm
Ski stance	1,077 mm
Track [Length x Width x Profile]	Cobra: 137 x 15 x 1.35 in.

COLOR

Sunburst Yellow / Black 

SUSPENSION

Front suspension	RAS™ 3
Front shock	Motion Control
Front suspension travel	220 mm
Rear suspension	SC™-5M
Center shock	Motion Control
Rear shock	HPG™
Rear suspension travel	245 mm

FEATURES

Frame	REV® Gen4
Bodywork	Wide design
Skis	Pilot™ DS 2
Seating	Trail with storage
Handlebar	U-shaped aluminum with J-hooks
Riser block height	120 mm
Starter	Electric
Reverse	Mechanical
Air radiator	
Brake system	Brembo brake with stainless-steel braided brake line
Heated throttle lever/grips	Standard
Gauge type	4.5 in. digital display
Windshield	360 mm
Runner - Carbide	Square 3/8 in - 102 mm
Bumpers (front/rear)	Std/Std

ski-doo

