

2022 *SPRING ONLY* RENEGADE® X-RS®

A hard-charging, race-inspired machine with the most advanced features and technology.



// WHAT'S NEW

- Smart-Shox semi-active suspension available
- Rotax® 900 ACE™ Turbo R with cable throttle housing and electro-mechanical reverse

// PACKAGE HIGHLIGHTS

- Rotax® 850 E-TEC® available
- High-performance KYB† PRO shock package
- 7.8 in. wide LCD display with BRP Connect available
- RAS™ X front suspension
- rMotion™ X rear suspension
- Electric starter
- RS running boards
- pDrive™ clutch
- Forward steering post position (850 E-TEC®)
- Rack steering system
- Forward adjustable riser
- Transparent handguards
- Open toe-hold
- Skis: Pilot™ X
- Backlit multifunction handlebar controls
- NEW standard with two sets of LinQ attachment points

RENEGADE® X-RS®
850 E-TEC® SHOWN

RENEGADE® X-RS®
900 ACE® TURBO R SHOWN

ROTAX® ENGINE	850 E-TEC®	900 ACE™ TURBO R
Engine details	Liquid-cooled, two-stroke, eRAVE™	Liquid-cooled, four-stroke D.O.H.C., dry sump, turbocharged
Horsepower	165	180
Cylinders – Displacement	2 – 849 cc	3 – 899 cc
Bore – Stroke	82 mm – 80.4 mm	73 mm – 69.7 mm
Carburation	E-TEC® direct injection with additional booster injectors	EFI
Fuel type – Octane	Unleaded – 95	Unleaded – 95
Fuel tank	36 L	36 L
Oil tank capacity	3.4 L	3.4 L

POWERTRAIN	850 E-TEC®	900 ACE™ TURBO R
Drive clutch	pDrive™ with clickers	pDrive™
Driven clutch	QRS Vent	QRS Vent
Drive sprocket pitch	73 mm	73 mm

DIMENSIONS	850 E-TEC®	900 ACE™ TURBO R
Overall vehicle length	3,038 mm	3,038 mm
Overall vehicle width	1,241 mm	1,241 mm
Overall vehicle height	1,222 mm	1,222 mm
Ski stance	1,077 mm	1,077 mm
Track (Length x Width x Profile)	Ice Ripper XT: 137 x 15 x 1.5 in.	Ice Ripper XT: 137 x 15 x 1.5 in.

COLOR	850 E-TEC®	900 ACE™ TURBO R
Sunburst Yellow / Black		
Black		

SUSPENSION	850 E-TEC®	900 ACE™ TURBO R
Front suspension	RAS™ X	RAS™ X
Front shock	KYB† PRO 36 Easy-Adjust	KYB† PRO Smart-Shox w/ opt. SAS
Front suspension travel	265 mm	265 mm
Rear suspension	rMotion™ X	rMotion™ X
Center shock	KYB† PRO 40 Easy-Adjust	KYB† PRO 40 Easy-Adjust
Rear shock	KYB† PRO Smart-Shox w/ opt. SAS	KYB† PRO Smart-Shox w/ opt. SAS
Rear suspension travel	292 mm	292 mm

FEATURES	850 E-TEC®	900 ACE™ TURBO R
Frame	REV® Gen4	REV® Gen4
Bodywork	Narrow design (2-stroke engines)	Wide design (4-stroke engines)
Skis	Pilot™ X	Pilot™ X
Seating	Trail performance (2-stroke engines)	Trail with storage (4-stroke engines)
Handlebar	U-shaped aluminum with J-hooks/Transparent handguards	U-shaped aluminum with J-hooks/Transparent handguards
Riser block height	Adjustable-120 mm	Adjustable-120 mm
Starter	Electric	Electric
Reverse	RER™ (850 E-TEC®)	Mechanical (900 ACE™ Turbo R)
Air radiator		
Brake system	Brembo racing brake with stainless-steel braided brake line	Brembo racing brake with stainless-steel braided brake line
Heated throttle lever/grips	Standard	Standard
Gauge type	7.2 in. wide digital display	7.8 in. wide LCD color display (opt.)
Windshield	210 mm	210 mm
Runner – Carbide	Round 1/2 – 102 mm	Round 1/2 – 102 mm
Bumpers (front/rear)	Std/Std	Std/Std

