

# 2022 SKANDIC® WT

Hardworking off-trail performance  
and towing capacity.



SKANDIC® WT  
900 ACE™ SHOWN

## // PACKAGE HIGHLIGHTS

- Rotax® 900 ACE™ engine with 650W magneto
- HPG™ rear shock
- 20 in. wide Multi-LinQ plate with 56.7 kg cargo capacity
- 4.5 in. digital display
- LTS telescopic front suspension
- SC™-5U articulating rear suspension with locking mechanism (no tool required)
- Removable passenger seat with grips
- 585 mm ultra-high windshield with side deflectors
- Hitch
- Air radiator with fan
- Standard electric start
- Deep-snow running boards with large openings
- Easy-shift transmission (H-L-N) with electro-mechanical reverse
- Pivoting mirrors
- pDrive™ clutch
- Low handlebar strap

### ROTAX® ENGINE

### 900 ACE™

Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Horsepower	95
Cylinders – Displacement	3 899 cc
Bore – Stroke	73 mm – 69.7 mm
Carburation	EFI
Fuel type – Octane	Unleaded 95
Fuel tank	42 L
Oil tank capacity	3.3 L

### POWERTRAIN

Drive clutch	pDrive™ with slider shoes
Driven clutch	QRS
Drive sprocket pitch	73 mm

### DIMENSIONS

Overall vehicle length	3,222 mm
Overall vehicle width	1,088 mm
Overall vehicle height	1,515 mm
Ski stance	889 mm
Track (Length x Width x Profile)	Cobra WT: 154 x 20 x 1.5 in.

### COLOR

Lava Red / Black

### SUSPENSION

Front suspension	LTS
Front shock	Motion Control
Front suspension travel	150 mm
Rear suspension	SC™-5U
Center shock	Motion Control
Rear shock	HPG™
Rear suspension travel	239 mm

### FEATURES

Frame	REV® Gen4
Bodywork	Wide design
Skis	Pilot™ 7.4
Seating	2-up modular with underseat storage
Handlebar	U-shaped aluminum with J-hooks/Low grab handle
Riser block height	145 mm
Starter	Electric
Reverse	Electro-mechanic
Air radiator	High-efficiency w/ fan
Brake system	Brembo brake with stainless-steel braided brake line
Heated throttle lever/grips	Standard (driver only)
Gauge type	4.5 in. digital display
Windshield	585 mm with mirrors
Runner – Carbide	Square 3/8 in. – 102 mm
Bumpers (front/rear)	Std/Heavy-duty with hitch

**ski-doo**

