# 2021

# SKANDIC SPORT NEW

# // WHAT'S NEW

- REV° Gen4 platform with wide-design bodywork
- Rotax® 600 EFI engine
- 4.5-in. digital display
- Pilot 7.4 skis
- and much more!

# // PACKAGE HIGHLIGHTS

- LTS telescopic front suspension
- SC™-5U articulating rear suspension with locking mechanism on one side (no tool required)
- 20 x 154 x 1.25 in. Utility WT track
- Standard electric start
- Medium (17 in.) windshield with air deflectors
- 1-up modular seat with rear storage
- pDrive™ clutch with slider shoes
- Deep snow running boards with large openings
- RER™ electronic reverse

Rear suspension travel



SKANDIC° SPORT 600 EFI SHOWN

ROTAX° ENGINE	600 EFI	
Engine details	Liquid-cooled, two-stroke	
Cylinders	2	
Displacement	599.4 cc / 36.6 in. <sup>3</sup>	
Bore	72.3 mm / 2.85 in.	
Stroke	73 mm / 2.87 in.	
Maximum engine speed	7,500 RPM	
Carburation	EFI	
Recommended fuel type	Regular unleaded	
Minimum octane	87	
Fuel tank	42 L / 11.1 US gal	
Oil tank capacity	3.4 L / 3.6 qt	
DRY WEIGHT	241 kg / 531 lb	
POWERTRAIN		
Drive clutch type	pDrive™ with slider shoes	
Driven clutch type	QRS	
Engagement	2,400 RPM	
Small sprocket number of teeth	21	
Large sprocket number of teeth	53	
D: 1 1 1 11	•	

•	
Bore	72.3 mm / 2.85 in.
Stroke	73 mm / 2.87 in.
Maximum engine speed	7,500 RPM
Carburation	EFI
Recommended fuel type	Regular unleaded
Minimum octane	87
Fuel tank	42 L / 11.1 US gal
Oil tank capacity	3.4 L / 3.6 qt
DRY WEIGHT	241 kg / 531 lb
POWERTRAIN	
Drive clutch type	pDrive™ with slider shoes
Driven clutch type	QRS
Engagement	2,400 RPM
Small sprocket number of teeth	21
Large sprocket number of teeth	53
Drive sprocket number of teeth	8
Drive sprocket diameter	185 mm / 7.2 in.
Drive sprocket pitch	75 mm / 2.86 in.
Brake system	Brembo brake with stainless-steel braided brake line
SUSPENSION	
Front suspension	LTS
Front shock	Motion Control
Front suspension travel	150 mm / 5.9 in.
Rear suspension	SC™-5U
Center shock	Motion Control
Rear Shock	HPG™

239 mm / 9.4 in.

# COLOR

Catalyst Grey / Black			
DIMENSIONS			
Vehicle overall length	3,259 mm / 129.3 in.		
Vehicle overall width	1,089 mm / 42.8 in.		
Vehicle overall height	1,369 mm / 53.9 in.		
Ski stance	889 mm / 35 in.		
Track (Length x Width x Profile)	Utility WT 154 x 20 x 1.25 in. (3,923 x 500 x 32 mm)		

# **FEATURES**

Frame	REV® Gen4
Bodywork	Wide design
Skis	Pilot™ 7.4
Seating	1-up modular with rear seat storage
Handlebar	U-shaped aluminum with J-hooks
Riser block height	145 mm / 5.7 in.
Starter	Electric
Reverse	RER™
Heated throttle lever / grips	Standard
Gauge type	4.5-in. digital display
Windshield	430 mm / 17 in.
Runner	Square 3/8
Carbide configuration	102 mm / 4 in. at 90°
Bumpers (Front/Rear)	Std / Std



SKANDIC° SPORT 600 EFI SHOWN

# // FEATURE HIGHLIGHTS



#### REV® Gen4 platform

Lightweight, strong and durable built to accommodate 20-in. wide tracks to maximize flotation and traction, while providing the precise handling and benefits of the open cockpit design. Maximum comfort and capability on- and off-trail.



#### SC<sup>™</sup>-5U articulating rear suspension

Features settings that maximize deep snow traction in reverse or lock out for towing.



#### Rotax® 600 EFI engine

600cc-class fuel injected engine delivering 85 horsepower and outstanding economy at an incredible value. Designed based on the 600R E-TEC with proven reliability and ease of ownership at its core with an outsized fun factor.



### LTS Front Suspension

Industry-exclusive telescopic front suspension enables a large, flat belly pan for exceptional deep snow flotation.



## Pilot™ 7.4 skis

Designed to provide better reverse capability, more floatation off trail and more positive steering on trail and while hauling loads.



4.5-in. digital display

All-digital LCD gauge cluster with flatter viewing angle for an easy-to-read info center whether standing or sitting.





©2020 Bombardier Recreational Products Inc., [BRP]. All rights reserved. ™, ® and the BRP logo are trademarks of BRP or its affiliates. Products are distributed in the USA by BRP US Inc. 'All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Printed in Canada