2021

EXPEDITION SE

// WHAT'S NEW

- Large panoramic 7.8-in. wide LCD color display
 available
- HPG front and center shocks

// PACKAGE HIGHLIGHTS

- Rotax® 900 ACE™ Turbo engine
- pDrive™ clutch
- REV° Gen4 platform with wide-design bodywork
- 20-in. wide Multi-LinQ plate with 56.7 kg cargo capacity
- SC™-5U articulating rear suspension with locking mechanism on one side (no tool required)
- Air Control Suspension (ACS)
- 20 x 154 track choices: 1.5 in. Silent Cobra WT or Silent Ice Cobra WT
- · Air radiator with fan
- RF D.E.S.S.™ key
- Electro-mechanical reverse

- Removable passenger seat and with heated grips
- Ultra large LinQ utility cargo box with 135 L of storage
- Hitch
- · High capacity battery
- Forward Adjustable Riser
- Gauge choices: 7.2-in. wide digital display or Large panoramic 7.8-in. wide LCD color display
- 27.5-in. Ultra-high windshield with side deflectors
- Pivoting mirrors
- Deep snow running boards with large openings
- Heated driver's visor power outlet
- Pilot 7.4 skis



EXPEDITION° SE 900 ACE™ TURBO SHOWN

// EXTRA HIGHLIGHTS

900 ACE™ TURBO WITH 650W MAGNETO

- Reversible throttle lever (thumb or finger activated) Engine oil cooler
- iTC™ Engine mapping modes (Standard, Sport or ECO°) High efficiency air radiator with fan

DOTAY® ENCINE	000 ACE™ Tba
ROTAX° ENGINE	900 ACE™ Turbo

	Liquid-cooled,	
	four-stroke D.O.H.C.,	
Engine details	dry sump, turbocharged	
Cylinders	3	
Displacement	899 cc	
Bore	74 mm	
Stroke	69.7 mm	
Maximum engine speed	7,300 RPM	
Carburation	EFI	
Recommended fuel type	Unleaded	
	95	
Fuel tank	42 L	
Oil tank capacity	3.3 L	
DOWEDEDALM		

POWERTRAIN

Drive clutch type	pDrive™
Driven clutch type	QRS
Engagement	2,000 RPM
Small sprocket number of teeth	Lo = 3.59:1 ratio
Large sprocket number of teeth	Hi = 2.0:1 ratio
Drive sprocket number of teeth	8
Drive sprocket diameter	183 mm
Drive sprocket pitch	73 mm
Brake system	Brembo brake with stainless-steel braided brake line

SUSPENSION

Front suspension	RAS™ 3
Front shock	HPG™
Front suspension travel	210 mm
Rear suspension	SC™-5U
Center shock	HPG™
Rear Shock	ACS (Air Control Suspension)
Rear suspension travel	239 mm

COLOR

Lava Red / Black

DIMENSIONS

Vehicle overall length 3,256 mm

Vehicle overall width 1,200 to 1,240 mm

Vehicle overall height 1,513 mm

Ski stance 975 or 1,020 mm

Track Silent Cobra WT: (Length x Width x Profile) 154 x 20 x 1.5 in. (3,923 x 500 x 38 mm) Silent Ice Cobra WT: 154 x 20 x 1.5 in. (3,923 x 500 x 38 mm) opt.

FEATURES

Frame	REV° Gen4
Bodywork	Wide design
Skis	Pilot™ 7.4
Seating	2-up modular with underseat storage
Handlebar	U-shaped aluminum with J-hooks / Low grab handle
Riser block height	Adjustable-120 mm
Starter	Electric
Reverse	Electro-mechanic
Heated throttle lever / grips	Standard (driver and passenger)
Gauge type	7.2-in. wide digital display 7.8-in. wide LCD color display (opt.)
Windshield	673 mm with mirrors
Runner	Square 3/8
Carbide configuration	102 mm at 90°
Bumpers (Front/Rear)	Heavy Duty / Hitch







EXPEDITION° SE 900 ACE™ TURBO SHOWN

// FEATURE HIGHLIGHTS



Rotax° 900 ACE™ Turbo engine

With a Rotax-built turbocharger specifically designed for the 900 ACE engine, riders get the technology they love with the reliable, powerful performance they demand in one advanced engine package.



Multi-LinQ plate

Standard LinQ adaptable storage. Fits 16- and 20-inch-wide LinQ accessories to maximize accessory options. Up to 56.7 kg cargo capacity.



Easy Shift transmission (H-L-N) with push-button reverse

Easily shifts with multiple gear ratios. Built for heavy duty reliability with high load resistance and optimal lubrication. Handlebar push-button engages electromechanical reverse.



SC[™]-5U articulating rear suspension

Features settings that maximize deep snow traction in reverse or lock out for towing.



Ultra large LinQ utility cargo box

135 L of lockable, weather resistant storage capacity. Incorporated hatchet and saw holder, plus attachment points for bungees and two 16-in. LinQ positions on top for expandable accessory use.