

2026 FREERIDE™

Extreme capacity deep snow sled built to live large, live free and go big. The Freeride™ is stable and predictable at higher speed in variable snow conditions, including bigger bumps.

// WHAT'S NEW

- REV® Gen5 Lightweight platform
- Improved Pilot™ DS 4 skis
- Super-short tunnel and radiator (for 154 in.)

// PACKAGE HIGHLIGHTS

- Premium LED headlights
- tMotion™ XT® rear suspension with rigid rear arm
- Reinforced rails
- E-TEC® SHOT™ starter standard
- Compact deep snow seat
- 10.25 in. touchscreen display with BRP Connect and built-in GPS
- RAS™ 3 front suspension with 930 mm (36 in.) ski stance



ROTAX® ENGINE

Engine details	850 E-TEC® TURBO R	850 E-TEC®
Cylinders – Displacement	Liquid-cooled, two-stroke, turbocharged, eRAVE™	Liquid-cooled, two-stroke, eRAVE™
Bore – Stroke		2 – 849 cc
Fuel System		82 x 80.4 mm
Fuel type – Octane	E-TEC® direct injection with additional booster injectors	
Fuel tank (L)		Premium unleaded – 95
Oil tank capacity (L)		36
		3.4

POWERTRAIN

Drive clutch	pDrive™ with clickers
Driven clutch	QRS Vent Plus
Drive sprocket pitch	73 mm (146 in.) 89 mm (154 in.)


DRY WEIGHT

Dry weight	211 kg (146 in.) 209 kg (154 in.)	203 kg (146 in.) 201 kg (154 in.)
------------	--------------------------------------	--------------------------------------

DIMENSIONS

Vehicle overall length	3,058 mm (146 in.) 3,188 mm (154 in.)
Vehicle overall width	1,073 mm (adjustable)
Vehicle overall height	1,395 mm
Ski stance	930 mm (adjustable)
Available tracks (in.) (Length x width x profile)	PowderMax®: 146 x 15 x 2.5 PowderMax® X-Light: 154 X 15 X 3.0

COLOR

Scandi Blue 

SUSPENSION

Front suspension	RAS 3
Front shock	KYB PRO 40 EA-3
Front suspension travel	215 mm
Rear suspension	tMotion XT with rigid rear arm
Center shock	KYB PRO 40 EA-3
Rear shock	KYB PRO 40 EA-3
Rear suspension travel	264 mm

FEATURES

Platform	REV® Gen5
Headlights	Premium LED
Skis	Pilot DS 4
Seating	Deep snow compact
Handlebar	Tapered with J-hooks / Grab handle
Riser block height	120 mm
Starter	E-TEC SHOT Starter
Reverse	RER™
Brake system	Brembo with adjustable lever
Heated throttle lever/grips	Standard
Gauge type	10.25 in. touchscreen display (std on 850 Turbo R) 4.5 in. digital display
Windshield	No
Runner (in.) – Carbide (in.)	3/8 square – 4
Bumpers (front/rear)	Standard / Standard

ski-doo

