
2026 BACKCOUNTRY[™] SPORT

For the value-oriented 50-50 rider wanting an advanced platform and modern engine technology.



- REV® Gen5 narrow platform
- REV Gen5 low opaque windshield
- High-performance LED headlights
- 2 options of ski stance: 39 in. for a true 50/50 on- and
- off-trail experience and 43 in. for a trail-oriented ride • 43 in. RAS X front suspension and Pilot 5.7 skis
- 2 choices of tracks: 2 in. PowderMax[†] track for 39 in., 1.5 in. Storm 150 track for 43 in. ski stance

• Pilot™ DS 2 skis (39 in. ski stance) and Pilot™ 5.7 skis

• cMotion™ X rear suspension

// PACKAGE HIGHLIGHTS

• Rotax® 600 EFI engine (43 in. ski stance only)

• 4.5 in. digital display

Electric starter

- Deep snow running boards with large openings
- U-shaped handlebar with integrated J-hooks
- Glove box with 1 US gal / 4 L of storage

• pDrive™ clutch

- Brembo brake
- Standard with 2 sets of LinQ attachment points

ROTAX ENGINE	600 EFI - 85
Engine details	Liquid-cooled, two-stroke
Horsepower*	85
Cylinders – Displacement	2 - 599.4 cc
Bore – Stroke (mm)	72.3 x 73
Fuel system	EFI
Fuel type – Octane	Regular unleaded - 87
Fuel tank (L/US gal)	36 / 9.5
Oil tank capacity (L/qt)	3.4 / 3.6
POWERTRAIN Drive clutch	pDrive / QRS
Driven clutch	
Drive sprocket pitch (mm/in.)	73 / 2.86
DRY WEIGHT	
Dry weight (lb)	447
DIMENSIONS	
Vehicle overall length (mm/in.)	3,174 / 125

Vehicle overall length (mm/in.)	3,174 / 125
Vehicle overall width (mm/in.)	1,160 / 45.7 (adjustable, 39 in.)
	1,211 / 47.8 (adjustable, 43 in.)
Vehicle overall height (mm/in.)	1,283 / 50.5
Ski stance (mm/in.)	1,000 / 39 (adjustable)
	1,090 / 43 (adjustable)
Available tracks (in.)	39 in. ski stance:
(Length x width x profile)	PowderMax [†] :
	146 x 16 x 2.0
	43 in. ski stance:
	Storm 150:
	146 x 15 x 1.5

COLOR

Neo Yellow

SUSPENSION

Front suspension	RAS™ X (39 in.)
	RAS X (43 in.)
Front shock	Motion Control
Front suspension travel	220 / 8.7 (39 in.)
(mm/in.)	235 / 9.3 (43 in.)
Rear suspension	cMotion X
Center shock	Motion Control
Rear shock	KYB 36
Rear suspension travel (mm/in.)	239 / 9.4

FEATURES

Platform	REV® Gen5
Headlights	High-performance LED
Skis	Pilot DS 2 Pilot 5.7
Seating	Trail narrow compact
Handlebar	U-shaped handlebar with integrated J-hooks
Riser block height (mm/in.)	120 / 4.7
Starter	Electric Starter
Reverse	RER™
Brake system	Brembo
Heated throttle lever/grips	Standard
Gauge type	4.5 in. digital display
Windshield	Low
Runner (in.) – Carbide (in.)	3/8 square – 4
Bumpers (front/rear)	Standard/Standard



BACKCOUNTRY SPORT 600 EFI SHOWN

2026 BACKCOUNTRY SPORT

//FEATURE HIGHLIGHTS



1 REV Gen5 narrow platform

A sleek design that brings a whole new level of refinement, performance and good looks to the trails.



2 RAS X front suspension with wider 43 in. ski stance

The Backcountry Sport equipped with the 43 in.-wide ski stance combined with the RAS X front suspension improves its on-trail cornering stability.



3 Rotax 600 EFI engine

600cc-class fuel injected engine delivering 85 horsepower and outstanding economy at an incredible value. Designed based on the 600R E-TEC® with proven reliability and ease of ownership at its core with an outsized fun factor.





4 cMotion X rear suspension

Completely new lighter design is better balanced for performance on- and off-trail. Perfectly balanced weight transfer for an increased fun factor and more travel for more comfort and bump absorption.



5 High-performance LED headlights Modern LED lighting allows for better nighttime vision and strong durability while maintaining low cost of ownership and energy efficiency.





6 Low opaque windshield

New light windshield that matches the modern look of the Gen5 platform. With esthetic deflector trims, textured for better scuff resistance and good wind protection.





©2025 Bombardier Recreational Products Inc., (BRP). All rights reserved. TM, * and the BRP logo are trademarks of BRP or its affiliates. Products are distributed in the USA by BRP US Inc. †All other trademarks are the property of their respective owners. Printed in Canada.