

2026 SKANDIC® SE

Spring-only package with ultimate off-trail traction and flotation loaded with premium utility features.



SKANDIC SE 900 ACE SHOWN

SKANDIC SE 900 ACE SHOWN

// PACKAGE HIGHLIGHTS

- Two Rotax® engines available: 600R E-TEC® and 900 ACE™ engines
- Available with four 20 in. or 24 in. track options
- Ultra-large LinQ utility cargo box
- Heated driver's visor power outlet
- 7.2 in. digital display
- Pilot™ 7.4 skis w/ liners
- KYB 36 center and rear shocks
- Multi-LinQ plate with 125 lb / 56.7 kg cargo capacity
- LTS telescopic front suspension
- SC™-5U articulating rear suspension with locking mechanism (no tool required)
- Removable passenger seat with grips
- Ultra-high windshield with side deflectors
- Air radiator with fan
- Standard electric start
- Deep snow running boards with large openings
- Easy Shift transmission (H-L-N) with RER™ electronic reverse (2 stroke) / electro-mechanical reverse (4 stroke)
- Pivoting mirrors
- pDrive™ clutch
- Low handlebar strap

ROTAX ENGINE

	600R E-TEC	900 ACE
Engine details	Liquid-cooled, two-stroke, eRAVE™	Liquid-cooled, four-stroke DOHC, dry sump
Horsepower*	125	95
Cylinders - Displacement	2 - 599.4 cc	3 - 899 cc
Bore - Stroke (mm)	72.3 x 73	73 x 69.7
Fuel system	E-TEC direct injection	EFI
Fuel type - Octane	Premium unleaded - 91	Regular unleaded - 87
Fuel tank (L/US gal)	42 / 11.1	42 / 11.1
Oil tank capacity (L/qt)	3.4 / 3.6	3.3 / 3.5

POWERTRAIN

	600R E-TEC	900 ACE
Drive clutch	pDrive with clickers / QRS [20 in.]	pDrive / QRS
Driven clutch	QRS Vent [24 in.]	
Drive sprocket pitch (mm/in.)	73 / 2.86	73 / 2.86

DRY WEIGHT

	600R E-TEC	900 ACE
Dry weight (lb)	651 [20 in.] 671 [24 in.]	675 [20 in.] 695 [24 in.]

DIMENSIONS

Vehicle overall length (mm/in.)	3,222 / 126.9
Vehicle overall width (mm/in.)	1,089 / 42.8
Vehicle overall height (mm/in.)	1,513 / 59.6
Ski stance (mm/in.)	889 / 35
Available tracks (in.) <small>(Length x width x profile)</small>	Silent Cobra WT: 154 x 20 x 1.8 Silent Ice Cobra WT: 154 x 20 x 1.5 Silent Cobra SWT: 154 x 24 x 1.5 opt. Silent Ice Cobra SWT: 154 x 24 x 1.5 opt.

COLOR

Catalyst Grey	
Black	

SUSPENSION

Front suspension	LTS
Front shock	Motion Control
Front suspension travel (mm/in.)	150 / 5.9
Rear suspension	SC-5U
Center shock	KYB 36
Rear shock	KYB 36
Rear suspension travel (mm/in.)	239 / 9.4

FEATURES

Platform	REV® Gen4
Headlights	Halogen
Skis	Pilot 7.4 with Liner
Seating	WideTrack 2-up
Handlebar	Standard with J-hooks / Grab handle
Riser block height (mm/in.)	145 / 5.7
Starter	Electric Starter
Reverse	RER (600R E-TEC) Electro-mechanical (900 ACE)
Air radiator	Fan
Brake system	Brembo
Heated throttle lever/grips	Standard (driver only)
Gauge type	7.2 in. digital display
Windshield	Ultra-high with mirrors
Runner (in.) - Carbide (in.)	3/8 square - 4
Bumpers (front/rear)	Heavy-duty/Hitch receiver

// FEATURE HIGHLIGHTS



1 Multi-LinQ plate

Standard LinQ adaptable storage. Fits 16- and 20-inch-wide LinQ accessories to maximize accessory options. Up to 135 lb (62.2 kg) cargo capacity.



2 Ultra large LinQ utility cargo box

135 L / 35.7 US gal of lockable, weather resistant storage capacity. Incorporated hatchet and saw holder, plus attachment points for bungees and two 16-in. LinQ positions on top for expandable accessory use.



3 LTS front suspension

Industry-exclusive telescopic front suspension enables a large, flat belly pan for exceptional deep snow flotation.



SKANDIC® SE 900 ACE™ SHOWN



4 Ski liners

Added flotation for extreme capability when your day takes you into the deep stuff.



5 20 in. and 24 in. wide tracks available

A wide range of options built to offer superb flotation and meet any towing needs.



6 SC-5U articulating rear suspension

The articulated rail maximizes deep snow traction in reverse and the toolless locking mechanism is ideal for towing.

ski-doo

