

2026 TUNDRA™ LE

Great off-trail and deep snow performance with light-utility capability.



TUNDRA LE 600 EFI SHOWN

// PACKAGE HIGHLIGHTS


- Rotax® 600 EFI and 600 ACE™ engine with 650W magneto available
- KYB 36 rear shock
- Painted tunnel
- 4.5 in. digital display
- LTS telescopic front suspension
- SC™-5U articulating rear suspension with locking mechanism (no tool required)
- Brembo brake
- Heavy-duty rear bumper with tongue type hitch
- Air radiator with fan
- Standard electric start
- Deep snow running boards with large openings
- Standard with 2 sets of LinQ attachment points
- Pilot™ DS 2 skis
- Low handlebar strap

ROTAX ENGINE	600 EFI – 85	600 ACE
Engine details	Liquid-cooled, two-stroke	Liquid-cooled, four-stroke DOHC, dry sump
Horsepower*	85	62
Cylinders – Displacement	2 – 599.4 cc	2 – 600 cc
Bore – Stroke (mm)	72.3 x 73	73 x 69.7
Fuel system	EFI	EFI
Fuel type – Octane	Regular unleaded – 87	Regular unleaded – 87
Fuel tank (L/US gal)	36 / 9.5	36 / 9.5
Oil tank capacity (L/qt)	3.4 / 3.6	2.1 / 2.2

POWERTRAIN	600 EFI – 85	600 ACE
Drive clutch	pDrive™ / QRS	eDrive™ 2 / QRS
Driven clutch		
Drive sprocket pitch (mm/in.)	73 / 2.86	73 / 2.86

DRY WEIGHT	600 EFI – 85	600 ACE
Dry weight (lb)	483	507

DIMENSIONS	600 EFI – 85	600 ACE
Vehicle overall length (mm/in.)	3,259 / 129.3	
Vehicle overall width (mm/in.)	994 / 39.1	
Vehicle overall height (mm/in.)	1,513 / 59.6	
Ski stance (mm/in.)	813 / 32	
Available tracks (in.)	Charger:	
<small>(Length x width x profile)</small>	154 x 16 x 1.5	

COLOR	600 EFI – 85	600 ACE
Black		

SUSPENSION	600 EFI – 85	600 ACE
Front suspension		LTS
Front shock		Motion Control
Front suspension travel (mm/in.)		150 / 5.9
Rear suspension		SC-5U
Center shock		Motion Control
Rear shock		KYB 36
Rear suspension travel (mm/in.)		239 / 9.4

FEATURES	600 EFI – 85	600 ACE
Platform		REV® Gen4
Headlights		Halogen
Skis		Pilot DS 2
Seating		Trail narrow compact
Handlebar		Standard with J-hooks / Grab handle
Riser block height (mm/in.)		145 / 5.7
Starter		Electric Starter
Reverse		RER™ (600 EFI) Mechanical (600 ACE)
Air radiator		Fan
Brake system		Brembo
Heated throttle lever/grips		Standard
Gauge type		4.5 in. digital display
Windshield		Medium
Runner (in.) – Carbide (in.)		3/8 square – 4
Bumpers (front/rear)		Standard/Heavy-duty

// FEATURE HIGHLIGHTS



1 Rotax 600 ACE and 600 EFI engines

Two easy to own, reliable and fuel-efficient choices. 62 hp*(600 ACE) or 85 hp*(600 EFI) versions ensure great performance and an incredible value.

*Observed HP metric based on internal dyno test in optimal conditions.



2 154 in. track length

Provides extra flotation and traction when riding in deep snow.



3 LTS front suspension

Industry-exclusive telescopic front suspension enables a large, flat belly pan for exceptional deep snow flotation.



TUNDRA LE 600 EFI SHOWN



4 Air radiator with fan

Extra cooling capacity when pulling heavy load, in low snow conditions or at low speed.



5 SC-5U articulating rear suspension

The articulated rail maximizes deep snow traction in reverse and the toolless locking mechanism is ideal for towing.



6 Heavy-duty rear bumper

For extra protection and extreme utility.

ski-doo

