

2018

# RENEGADE® X

## PACKAGE HIGHLIGHTS

- RAS™ 2 front suspension
- REV-XS™ platform
- rMotion™ rear suspension
- 15 x 137 x 1.75 (381 x 3487 x 44.5 mm) PowderMax track
- KYB† Pro 36 aluminum piggyback rear shock with Easy-Adjust compression adjusters (22 clics)
- HPG™ Plus R aluminum front shocks with no-tool rebound adjuster (22 clics)
- RER™ electronic reverse
- Engine temperature gauge
- Backlit multifunction steering controls
- RF D.E.S.S.™ key
- REV-XP™ X seat with 5 L of storage
- Transparent handguards

## EXTRA HIGHLIGHTS

- iTC™ Engine mapping modes (Standard, Sport or ECO)
- Reversible throttle lever (thumb or finger activated)
- Learning-Key included
- Mechanical reverse
- Extended heat exchanger for better cooling capacity
- Engine oil cooler
- Heavy duty bumper



RENEGADE® X 1200 4-TEC shown

European model is equipped with other skis than displayed

## ROTAX® ENGINE

### 1200 4-TEC

Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	3
Displacement	1170.7 cc
Bore	91 mm
Stroke	60 mm
Maximum engine speed	7800 RPM
Carburation	EFI
Recommended fuel type	Regular unleaded
Minimum octane	95
Fuel tank	40 liters
Oil tank capacity	3.5 liters

## POWERTRAIN

Drive clutch type	eDrive™ 2
Driven clutch type	QRS
Engagement	2200 RPM
Small sprocket number of teeth	24
Large sprocket number of teeth	45
Drive sprocket number of teeth	8
Drive sprocket diameter	183 mm
Brake system	Brembo racing brake with stainless-steel braided brake line

## COLOUR

Black 

## DIMENSIONS

Vehicle overall length	3110 mm
Vehicle overall width	1217 mm
Vehicle overall height	1210 mm
Ski stance	1077 mm
Ski overall length	1066 mm
Track nominal width	381 mm
Track nominal length	3487 mm
Track profile height	44.5 mm PowderMax†

## SUSPENSION

Front suspension	RAS™ 2
Front shock	HPG™ Plus R
Front suspension max. travel	229 mm
Rear suspension	rMotion™
Center shock	HPG™ Plus
Rear shock	KYB† Pro 36 EA
Rear suspension max. travel	270 mm

## FEATURES

Frame	REV-XS™	Starter	Electric	Mirrors	Optional
Skis	Pilot™ DS 2	Reverse	Mechanical	Windshield	285 mm
Seating	REV-XP™ X with storage	Heated throttle lever	Standard	Runner	Square 5/16
Handlebar	Aluminum with J-hooks	Heated grips	Standard	Carbide configuration	102 mm at 90°
Riser block height	130 mm	Gauge	Multifunction	Hitch	Optional