

2019 RENEGADE® X-RS®

PACKAGE HIGHLIGHTS

- pDrive™ clutch
- RAS™ 3 front suspension
- REV® Gen4 platform with narrow-design (850 E-TEC®) or **wide-design (900 ACE™ Turbo)** bodywork
- rMotion™ rear suspension
- Forward Adjustable Riser
- KYB® Pro 36 R front shocks and KYB® Pro 40 rear shocks aluminum piggyback with Easy-Adjust compression adjuster (22 clicks)
- Brembo racing brake with braided stainless-steel brake line
- RER™ electronic reverse (850 E-TEC®) / Mechanical reverse (900 ACE™ Turbo)
- RF D.E.S.S.™ key
- Transparent handguards
- Backlit multifunction steering controls
- Multifunction digital gauge with display

- Open toe-hold
- RS running boards
- Forward steering position (850 E-TEC®)
- Rack steering system
- 381 x 3,487 x 40.6 mm (15 x 137 1.6 in.) Ice Cobra track
- Ergo-Step side panels

EXTRA HIGHLIGHTS

- 900 ACE™ Turbo**
- **iTC™ Engine mapping modes (Standard, Sport or ECO®)**
 - **Reversible throttle lever (thumb or inger activated)**
 - **Engine oil cooler**

Renegade® X-RS®
850 E-TEC®
with Adjustable
Package shown

(Adjustment package
not available in Europe)



Renegade® X-RS®
900 ACE™
TURBO shown

ROTAX® ENGINE

	850 E-TEC®	900 ACE™ TURBO
Engine details	Liquid-cooled, eRAVE™	Liquid-cooled, four-stroke DOHC, turbocharged
Cylinders	2	3
Displacement	849 cc	899 cc
Bore	82 mm	74 mm
Stroke	80.4 mm	69.7 mm
Maximum engine speed	7,900 RPM	7,750 RPM
Carburation	E-TEC direct injection with additional booster injectors	EFI
Recommended fuel type	Unleaded	Unleaded
Minimum octane	95	95
Fuel tank	36 L	36 L
Oil tank capacity	3.4 L	3.3 L

POWERTRAIN

	850 E-TEC®	900 ACE™ TURBO
Drive clutch type	pDrive™ with clickers	pDrive™
Driven clutch type	QRS	QRS-MSS vent
Engagement	3,600 RPM	2,200 RPM
Small sprocket number of teeth	23	25
Large sprocket number of teeth	45	45
Drive sprocket number of teeth	8	8
Drive sprocket diameter	183 mm	183 mm
Brake system	Brembo racing brake with stainless-steel braided brake line	Brembo racing brake with stainless-steel braided brake line

DRY WEIGHT

228 kg

247 kg

FEATURES

Frame	REV® Gen4
Bodywork	Narrow design (850 E-TEC®) Wide design (900 ACE™ Turbo)
Skis	Pilot™ DS 2
Seating	Trail performance (850 E-TEC®) Trail with storage (900 ACE™ Turbo)
Handlebar	U-shaped aluminum with J-hooks

Riser block height	Adjustable-120 mm
Starter	Electric
Reverse	RER™ (850 E-TEC®) Mechanical (900 ACE™ Turbo)
Heated throttle lever/ grips	Standard
Gauge	Multifunction

Mirrors	Optional
Windshield	N/A
Runner	Round 7/16
Carbide configuration	102 mm at 90°
Hitch	Optional

COLOR

Orange Crush / Hyper Silver (Spring only)

Black

DIMENSIONS

Vehicle overall length	3,014 mm
Vehicle overall width	1,217 mm
Vehicle overall height	1,222 mm
Ski stance	1,077 mm
Ski overall length	1,066 mm
Track nominal width	381 mm
Track nominal length	3,487 mm
Track profile height	40.6 mm Ice Cobra

SUSPENSION

Front suspension	RAS™ 3
Front shock	KYB® Pro 36 R Easy-Adjust
Front suspension max. travel	255 mm
Rear suspension	rMotion™
Center shock	KYB® Pro 40 Easy-Adjust
Rear shock	KYB® Pro 40 Easy-Adjust
Rear suspension max. travel	270 mm