

2017

RENEGADE[®] ADRENALINE

PACKAGE HIGHLIGHTS

- RAS™ 2 front suspension
- REV-XS™ platform
- rMotion™ rear suspension
- 15 × 137 × 1.25 in. RipSaw[†] track
- HPG™ Plus aluminum front shocks
- Pilot™ 5.7 skis
- Brembo brake with braided stainless-steel brake line
- RER™ electronic reverse
- Analog gauge with display
- Electric fuel gauge
- 15 in. / 38cm windshield with integrated hand wind deflectors
- Painted tunnel
- RF D.E.S.S.™ key

EXTRA HIGHLIGHTS

- 900 ACE & 1200 4-TEC**
- Mechanical reverse
 - Reversible throttle lever (thumb or finger activated)
 - iTC™ Engine mapping modes (Standard, Sport or ECO)
 - Engine oil cooler
 - Learning-Key included
- 1200 4-TEC only**
- Extended heat exchanger for better cooling capacity



600 H.O. E-TEC shown

ROTAX® ENGINE

	600 H.O. E-TEC [®]	900 ACE	1200 4-TEC
Engine details	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., dry sump	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	3	3
Displacement	594.4 cc / 36.3 in. ³	899.0 cc / 54.9 in. ³	1170.7 cc / 71.4 in. ³
Bore	72 mm / 2.8 in.	74 mm / 2.9 in.	91 mm / 3.6 in.
Stroke	73 mm / 2.9 in.	69.7 mm / 2.7 in.	60 mm / 2.4 in.
Maximum engine speed	8100 RPM	7250 RPM	7800 RPM
Carburation	Electronic Direct Injection	EFI	EFI
Recommended fuel type	Premium unleaded	Regular unleaded	Regular unleaded
Minimum octane	91	87	87
Fuel tank	40 liters / 10.6 gallons	40 liters / 10.6 gallons	40 liters / 10.6 gallons
Oil tank capacity	3.7 liters / 3.9 quarts	3.3 liters / 3.5 quarts	3.5 liters / 3.7 quarts

POWERTRAIN

	TRA™ III	eDrive™ 2	eDrive™ 2
Drive clutch type	QRS	QRS (short shaft)	QRS
Engagement	3400 RPM	2200 RPM	2200 RPM
Small sprocket number of teeth	23	24	24
Large sprocket number of teeth	45	49	45
Drive sprocket number of teeth	8	8	8
Drive sprocket diameter	183 mm / 7.2 in.	183 mm / 7.2 in.	183 mm / 7.2 in.
Brake system	Brembo brake with braided stainless-steel brake line	Brembo brake with braided stainless-steel brake line	Brembo brake with braided stainless-steel brake line

DRY WEIGHT

216 kg / 477 lb	228 kg / 503 lb	239 kg / 528 lb
-----------------	-----------------	-----------------

COLOUR

White / Orange Crush 

Black 

DIMENSIONS

Vehicle overall length	3110 mm / 122.4 in.
Vehicle overall width	1217 mm / 47.9 in.
Vehicle overall height	1210 mm / 47.6 in.
Ski stance	1077 mm / 42.4 in.
Ski overall length	1066 mm / 42 in.
Track nominal width	381 mm / 15 in.
Track nominal length	3487 mm / 137 in.
Track profile height	31.8 mm / 1.25 in. RipSaw [†]

SUSPENSION

Front suspension	RAS™ 2
Front shock	HPG™ Plus
Front suspension max. travel	220 mm / 8.7 in.
Rear suspension	rMotion™
Center shock	HPG™
Rear shock	HPG™
Rear suspension max. travel	270 mm / 10.6 in.

FEATURES

Frame	REV-XS™	Reverse	RER™ (600 H.O.), Mechanical (900 ACE, 1200 4-TEC)	Mirrors	Optional
Skis	Pilot™ 5.7	Heated throttle lever	Standard	Windshield	375 mm / 15 in.
Seating	REV-XP™ X with storage	Heated grips	Standard	Runner	Square 5/16
Handlebar	Aluminum with J-hooks	Gauge	Analog with display	Carbide configuration	102 mm / 4 in. at 90°
Riser block height	115 mm / 4.5 in.	Electric start	Standard	Hitch	Optional



1200 4-TEC shown



600 H.O. E-TEC shown

FEATURE HIGHLIGHTS



RAS™ 2 Front suspension

A taller ski spindle, refined geometry and lighter components sharpen the sled's already precise handling, especially in extreme conditions.



RF D.E.S.S.™ Key

D.E.S.S.™ security system on most models uses Radio Frequency technology for peace of mind. The ball-and-socket design ensures a solid connection in all conditions.



rMotion™ suspension

Sets new standards in comfort, capability and adjustability.



LinQ™ cargo system (option)

Our cargo attachment system is the hassle-free way to connect cargo bags or a fuel caddy to your sled in seconds.



Analog gauge with display

GAUGE FEATURES

Speedometer	Standard
Tachometer	Standard
Fuel	Standard
Engine temperature	Optional